Datasheet



eyetv netstream 4Sat

DVB-S2 Network Tuner with Hardware Transcoding

Satellite TV anywhere in your home

Forget about cabling:

EyeTV Netstream 4Sat makes satellite TV simply part of your home network.

Enjoy HD satellite TV on any tablet, smartphone, computer or certified SAT>IP receiver in your home and even on your patio or in your garden. Free apps for iPad, iPhone, Kindle Fire, and Android make setup a breeze — and with

4 receivers, everyone in your home can watch their favorite program with EyeTV Netstream 4Sat.

What's Included

- EyeTV Netstream 4Sat DVB-S2 Network Tuner with Hardware Transcoding
- Ethernet cable
- Power supply
- Quick Start Guide

System Requirements

- Satellite dish with digital universal LNB or DiSEqC multiswitch (not included)
- 1000BASE-T Gigabit Ethernet (802.11n for Wi-Fi)

Supported Devices

- iOS: iPad Air, iPad (iPad 2 or later), iPad mini, iPhone (iPhone 4S or later) or iPod touch (4th generation or later); with iOS 7.0.4 or later
- Android:
- Amazon: Kindle Fire (2nd generation), Kindle Fire HD, HDX
- Google: Galaxy Nexus, Nexus 4, Nexus 5, Nexus 7, Nexus10
- HTC: One S. One X
- Samsung Galaxy: Note, Note II, S II, S III, S4, S5, S III mini, S4 mini. Tab 2. Tab 3 8.0

EyeTV Netstream 4Sat requires an Android device with a 1 GHz or faster dual-core ARM CPU and Android 4.0.3 ("Ice Cream Sandwich") or later. Playback of MPEG-4/H.264 video requires a processor with NEON support (e.g. Tegra3).

- Mac: OS X 10.9 or later
- PC: Windows 7 or later, 2 GHz Intel Core 2 Duo (or comparable), sound card
- TV: SAT>IP-certified receiver link:

Notes:

- For initial setup of EyeTV Netstream 4Sat, an iOS or Android device is required.
- Encrypted channels are not supported on tablets, smart phones and computers. Some SAT>IP receivers support encrypted channels: please ask the manufacturer of your receiver for further information.
- Performance may be limited by network bandwidth.
 802.11n network required for wireless streaming.

Technical Specifications

Tuner Technology

- DVB-S, DVB-S2
- Digital Universal LNB: Single, Twin/Dual, Quad or Quattro
- Unicable
- Integrated multiswitch
- DiSEqC 1.0

Connectivity

- Satellite inputs (4): F connector for RG-6/U coaxial satellite cable
- Network: RJ45 1000BASE-T Gigabit Ethernet
- Power: DC 12V 3A

Weight & Dimensions

- Dimensions: 25 x 12.6 x 4.1 cm
- Weight: 806 g
- Suitable for wall mounting